

MODEL 2150




EXCESS FLOW VALVE

The Model 2150 Excess Flow Valve has female NPT connections on the inlet side and female NPT connections on the outlet side. The 2150 is designed for use in liquid or vapor service to stop the flow in the event of a sudden flow rate change. These valves offer excellent flow rates and can be used in many different applications. Options include an external manual bypass that allows for faster equalization across the poppet. Can be used with standard poppet or soft seat with no weep hole.

NPS	2130	2140	2150	2160	2170	2155	2180
0.75"	4.00"	4.00"	4.00"	4.00"	4.00"	6.00"	4.00"
1	4.00	4.00	4.00	4.00	4.00	6.00	4.00
1.5	4.50	4.50	4.50	4.50	4.50	6.50	4.50
2	5.63	5.63	5.63	5.63	5.63	7.63	5.63
3	7.25	7.25	7.25	7.25	7.25	9.25	7.25
4	9.00	9.00	9.00	9.00	9.00	11.00	9.00

These dimensions are for standard designs as reference only.
Valves can be custom-engineered as needed.

Typical dimensions are listed. Data contained herein can be altered to accommodate design changes and changes to increase performance.
Information on this page is the sole property of L6 Inc. d/b/a Total Valve Systems



Basic options include carbon steel bodies & stainless internals with other materials & pressure classes available upon request.